

Free Questions for MTCNA by vceexamstest

Shared by Matthews on 20-10-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

You can not use OSPF and RIP routing protocols simultaneously on the RouterOS.

Options:			
A- FALSE			
B- TRUE			
Answer:			
A			

Question 2

Question Type: MultipleChoice

The correct order for PPPOE discovery stage is

Options:

- A- Initialization, Session confirmation, Request and Offer
- B- Initialization, Offer, Request and Session confirmation
- C- Request, Initialization, Session confirmation and Offer
- D- Request, Offer, Initialization and Session confirmation

Answer:			
В			

Question 3

Question Type: MultipleChoice

If 'check-gateway' is enabled for an ECMP route and one of the gateways is unreachable, then:

Options:

A- ECMP is going to send packets to all gateways even if one is unreachable.

- **B-** The unreachable gateway is not going be used in Round Robin algorithm.
- C- The ECMP route becomes inactive.

Answer:

В

Question 4

Question Type: MultipleChoice

Mangle Routing (routing-mark) is possible, by using chains:

Options:

A- prerouting and output

- B- forward and output
- C- prerouting and forward
- **D-** input and output
- E- forward and postrouting

В

Question 5

Question Type: MultipleChoice

Select all tunnels that support authentication of clients with a username and password.

Options:		
A- PPPoE		
B- OpenVPN		
C- IPIP		
D- PPTP/L2TP		
E- EoIP		

Answer:

А

Question 6

Question Type: MultipleChoice

A client uses a RouterBOARD1000. The clock is configured in '/system clock'. The clock resets to default after each reboot.

Select the best solution for the problem.

Options:

- A- Write a script in '/system script' to set the clock
- B- Configure '/system ntp server' and set a valid and reachable NTP client address.
- C- Configure '/system ntp client' and set a valid and reachable NTP server address.
- **D-** Open the router and ensure the CMOS battery is fine.

Answer:

С

Question 7

Question Type: MultipleChoice

Which of the protocols below is used by Netinstall?

Options:			
A- arp			
B- bootp			
C- dhcp			
D- rarp			

Answer:

В

Question 8

Question Type: MultipleChoice

NAT rule is going to catch SMTP traffic and send it to a specific mail server.

What is the correct action for a NAT rule?

Options:		
A- passthrough		
B- dst-nat		
C- redirect		
D- tarpit		

Answer:

В

Question 9

Question Type: MultipleChoice

Action=redirect is applied in

Options:

A- chain=srcnat

B- chain=forward

C- chain=dstnat

Answer:

С

Question 10

Question Type: MultipleChoice

Router has wireless and ethernet client interfaces, all client interfaces are bridged. To create a DHCP service for all clients, DHCP server must be configured on:

Options:

- A- Ethernet and wireless interfaces
- B- DHCP service is not possible in this setup
- C- Every bridge port
- D- Only on the bridge interface

Answer:

D

To Get Premium Files for MTCNA Visit

https://www.p2pexams.com/products/mtcna

For More Free Questions Visit

https://www.p2pexams.com/mikrotik/pdf/mtcna

