



Free Questions for NCM-MCI-5.15 by vceexamstest

Shared by Reed on 06-06-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

An administrator is trying to correct high cluster IOPs and Cluster Controller Latency. Networking is the suspected issue.

Which networking parameters should be configured in the Nutanix cluster?

Options:

- A- Bond State and network latency
- B- Number of NICs connected and network latency.
- C- Number of NICs connected and frame size
- D- Number of NICs connected and bond state.

Answer:

C

Question 2

Question Type: MultipleChoice

A CEO asks the IT administrator to provide a list of required resources to protect current workloads and the two new SQL servers from a disaster. The Nutanix environment is managed by Prism Central.

Which option explains how to meet the CEO's request?

Options:

A- In Capacity Runway, select Optimize Resources and select all VMs that must be protected.

B- Create a new project and assign the VMs to it to get compute and storage requirements.

C- Create a new scenario based on a new cluster based on a VM Profile and select Recommend.

D- Create a new Recovery policy by selecting the VM that needs to be protected and get hardware requirements.

https://portal.nutanix.com/page/documents/details?targetId=Prism-Central-Guide-Prism-v5_19:mul-resource-planning-scenario-create-pc-t.html#ntask_lhn_hlp_qx

Answer:

C

Question 3

Question Type: MultipleChoice

An administrator is deploying a new application to a Nutanix Enterprise Cloud. The application requires a security to prevent unauthorized access. The application also uses many non-standard ports that are unique to it. Security should not be changed for existing applications.

What should the administrator do to meet these requirement?

Options:

- A-** Use existing categories for the VMs. and create new security policies to use the existing categories.
- B-** Use existing categories for the VMs and modify existing security policies to include the specific port.
- C-** Create new categories for the VMs, and create new security policies that include the new categories.
- D-** Create new categories for the VMs, and modify existing security policies to include the new categories.

Answer:

C

Question 4

Question Type: MultipleChoice

An administrator has a 32-node hybrid cluster with CPU, RAM and storage utilization of 80%. A database VM is configured with VM Flash.

What is causing this IO latency?

Options:

- A- Controller VM is experiencing high CPU ready time.
- B- Curator scans causes by ILM constantly moving data.
- C- VM Flash Mode reduces SSD tier capacity for VMs.
- D- Database VM is experiencing high CPU ready time.

Answer:

A

Question 5

Question Type: MultipleChoice

The networking team makes changes to the Top of Rack switches to which the Nutanix cluster are attached. A few VMs are able to communicate with each other on the same node but are unable to connect to other parts of the network.

What is the likely cause of this issue?

Options:

- A- There is a VLAN misconfiguration on the VMs.
- B- The vNIC port is disconnected on the affected VMs.
- C- There is a VLAN misconfiguration on the switch.
- D- Jumbo Frame are misconfigured across ports.

Answer:

C

Question 6

Question Type: MultipleChoice

Refer to the exhibit.

An administrator logged into Prism Element, notices the following in the home dashboard, and showing the exhibit.

Which action should the administrator take next?

Options:

- A- Configure the fqdn for the hosts indicated
- B- Troubleshoot the zookeeper server issue
- C- Re-run NCC specifying data_resiliency_check
- D- Check the hardware page for disk failures

Answer:

C

Question 7

Question Type: MultipleChoice

A customer has a four-node cluster and is using Volume Groups to provide storage services to a SQL cluster.

In the event of a CVM failure in the cluster, what is the expected IO path of the volume group's iSCSI targets?

Options:

- A- vDisk directed at failure CVM are redirected to Data Services IP until CVM is reconnected
- B- vDisk directed to CVM that failed to disconnect and will not reconnect without manual intervention
- C- vDisk directed to failed CVM are redirected to another CVM and automatically reconnect
- D- vDisk directed at failed CVM will disconnect and reconnect when the failed CVM comes back online

Answer:

C

Question 8

Question Type: MultipleChoice

A customer has the following requirement for a Nutanix cluster:

Must support high-performance Nutanix Volumes iSCSI workloads

Must utilize AHV nodes

Must use 10 GbE interface

How should the customer optimize networking?

Options:

- A- Enable Jumbo Frame on just the Host
- B- Convert Cluster to ESXi and enable Jumbo Frame on Host and CVM
- C- Enable Jumbo Frames on just the CVM
- D- Enable the use of Jumbo Frame on Host and CVM

Answer:

A

To Get Premium Files for NCM-MCI-5.15 Visit

<https://www.p2pexams.com/products/ncm-mci-5.15>

For More Free Questions Visit

<https://www.p2pexams.com/nutanix/pdf/ncm-mci-5.15>

