



VMware VCAP-NV Deploy 3V0-41.22 Practice Questions

Shared by Mathews on 17-08-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page



Question 1

Question Type: MultipleChoice

SIMULATION

Task 13

You have been asked to configure the NSX backups for the environment so that if the NSX Manager fails it can be restored with the same IP address to the original primary Data Center that is in an Active / Standby configuration. Backups should be scheduled to run once every 24 hours as well as when there are changes published to the NSX environment. Ensure that backups are completed on their respective environment. Verify the backup file has been created on the SFTP server.

* Credentials needed to complete the task:

SFTP User:	sftpuser
Password:	VMware!!
SFTP IP:	192.168.110.91
Hostname:	ubuntu-01.corp.local

You need to:

- * Verify that an SFTP server is available on the network and obtain SFTP Fingerprint.
- * Configure NSX Backups via NSX Appliance Backup
- * Configure Scheduling Criteria

Backup Configuration Criteria

Backup Schedule:	Once backup per 24 hours
Additional Backup Triggers:	Detect NSX configuration (5 min time interval)
Primary Data Center Configuration:	Active / Standby
Backup locations:	All backups on respective NSX environment
Additional Notes:	NSX Manager shall be restored with same IP address
Directory Path:	/data
Passphrase:	VMware!!

Complete the requested task.

Notes: Passwords are contained in the user_readme.txt. This task is not dependent on other tasks. This task should take approximately 15 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To configure the NSX backups for the environment, you need to follow these steps:

Verify that an SFTP server is available on the network and obtain SFTP fingerprint. You can use the `search_web('SFTP server availability')` tool to find some information on how to set up and check an SFTP server. You can also use the `ssh-keyscan` command to get the fingerprint of the SFTP server. For example, `ssh-keyscan -t ecdsa sftp_server` will return the ECDSA key of the `sftp_server`. You can compare this key with the one displayed on the NSX Manager UI when you configure the backup settings.

Configure NSX Backups via NSX Appliance Backup. Log in to the NSX Manager UI with admin credentials. The default URL is `https://<nsx-manager-ip-address>`. Select System > Lifecycle Management > Backup & Restore. Click Edit under the SFTP Server label to configure your SFTP server. Enter the FQDN or IP address of the backup file server, such as 10.10.10.100. The protocol text box is already filled in. SFTP is the only supported protocol. Change the default port if necessary. The default TCP port is 22. In the Directory Path text box, enter the absolute directory path where the backups will be stored, such as `/dat`

a. The directory must already exist and cannot be the root directory (`/`). Avoid using path drive letters or spaces in directory names; they are not supported. In the Passphrase text box, enter a passphrase that will be used to encrypt and decrypt the backup files, such as `VMware1!`. Click Save to create the backup configuration.

Configure Scheduling Criteria. On the Backup & Restore page, click Edit under the Schedule label to configure your backup schedule. Select Enabled from the drop-down menu to enable scheduled backups. Select Daily from the Frequency drop-down menu to run backups once every 24 hours. Select a time from the Time drop-down menu to specify when the backup will start, such as 12:00 AM. Select Enabled from the Additional Backup Trigger drop-down menu to run backups when there are changes published to the NSX environment. Click Save to create the backup schedule.

Verify that a backup file has been created on the SFTP server. On the Backup & Restore page, click Start Backup to run a manual backup and verify that it completes successfully. You should see a message saying "Backup completed successfully". You can also check the status and details of your backups on this page, such as backup size, duration, and timestamp. Alternatively, you can log in to your SFTP server and check if there is a backup file in your specified directory path, such as `/data`.

Question 2

Question Type: MultipleChoice

SIMULATION

Task 12

An issue with the Tampa web servers has been reported. You would like to replicate and redirect the web traffic to a network monitoring tool outside Of the NSX-T environment to further analyze the traffic.

You are asked to configure traffic replication to the monitoring software for your Tampa web overlay segments with bi-directional traffic using this detail:

Session Name:	Network-Monitor-01
Network Appliance Name/Group:	NM-01
Direction:	Bi Directional
TCP/IP Stack:	Default
Encapsulation Type:	GRE

Complete the requested configuration.

Notes: Passwords are contained in the user_readme.txt. This task is not dependent on other tasks. This task should take approximately 10 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To configure traffic replication to the monitoring software for your Tampa web overlay segments with bi-directional traffic, you need to follow these steps:

Log in to the NSX Manager UI with admin credentials. The default URL is <https://<nsx-manager-ip-address>>.

Navigate to Networking > Segments and select the Tampa web overlay segment that you want to replicate the traffic from. For example, select Web-01 segment that you created in Task 2.

Click Port Mirroring > Set > Add Session and enter a name and an optional description for the port mirroring session. For example, enter Tampa-Web-Monitoring.

In the Direction section, select Bi-directional as the direction from the drop-down menu. This will replicate both ingress and egress traffic from the source to the destination.

In the Source section, click Set and select the VMs or logical ports that you want to use as the source of the traffic. For example, select Web-VM-01 and Web-VM-02 as the source VMs. Click Apply.

In the Destination section, click Set and select Remote L3 SPAN as the destination type from the

drop-down menu. This will allow you to replicate the traffic to a remote destination outside of the NSX-T environment.

Enter the IP address of the destination device where you have installed the network monitoring software, such as 10.10.10.200.

Select an existing service profile from the drop-down menu or create a new one by clicking New Service Profile. A service profile defines the encapsulation type and other parameters for the replicated traffic.

Optionally, you can configure advanced settings such as TCP/IP stack, snap length, etc., for the port mirroring session.

Click Save and then Close to create the port mirroring session.

[You have successfully configured traffic replication to the monitoring software for your Tampa web overlay segments with bi-directional traffic using NSX-T Manager UI.](#)

Question 3

Question Type: MultipleChoice

SIMULATION

Task 16

You are working to automate your NSX-T deployment and an automation engineer would like to retrieve your BOP routing information from the API.

You need to:

- * Run the GET call in the API using Postman
- * Save output to the desktop to a text file called API.txt

Complete the requested task.

Notes: Passwords are contained in the user _ readme.txt. This task is not dependent on another. This task should take approximately 5 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To run the GET call in the API using Postman and save the output to the desktop to a text file called API.txt, you need to follow these steps:

Open Postman and create a new request tab. Select GET as the method from the drop-down menu.

Enter the URL of the NSX-T Policy API endpoint for retrieving the BGP routing table, such as `https://<nsx-manager-ip-address>/policy/api/v1/infra/tier-0s/vmc/routing-table?enforcement_point_path=/infra/sites/default/enforcement-points/vmc-enforcementpoint`

Click the Authorization tab and select Basic Auth as the type from the drop-down menu. Enter your NSX-T username and password in the Username and Password fields, such as admin and VMware1!.

Click Send to execute the request and view the response in the Body tab. You should see a JSON object with the BGP routing table information, such as routes, next hops, prefixes, etc.

Click Save Response and select Save to a file from the drop-down menu. Enter API.txt as the file name and choose Desktop as the location. Click Save to save the output to your desktop.

[You have successfully run the GET call in the API using Postman and saved the output to your desktop to a text file called API.txt.](#)

Question 4

Question Type: MultipleChoice

SIMULATION

Task 6

You are asked to integrate NSX manager with LDAP to better control NSX administrators' roles and responsibilities. Ensure users can manage the NSX environment utilizing Active Directory login credentials.

You need to:

* Configure NSX Manager LDAP integration to the corp.local domain using the following configuration detail:

• Configure NSX Manager LDAP integration to the corp.local domain using the following configuration detail:	
LDAP identity source name:	corp.local
Domain Name:	corp.local
BASE DN:	DC=corp, DC=local
Type:	Active Directory over LDAP
Active Directory host name:	controlcenter.corp.local
LDAP Protocol:	LDAP
LDAP Port:	389
User Start TLS:	disabled
Bind identity user name:	administrator@corp.local
Bind identity password:	VMware!!

* Configure the user nsx-admin@corp.local Active Directory account as an Enterprise Admin access role.

Complete the requested task.

Notes:

Passwords are contained in the user_readme.txt. You may want to move to other tasks/steps while waiting for configuration changes to be applied. This task should take approximately 15 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To integrate NSX Manager with LDAP to better control NSX administrators' roles and responsibilities, you need to follow these steps:

Log in to the NSX Manager UI with admin credentials. The default URL is `https://<nsx-manager-ip-address>`.

Navigate to System > User Management > LDAP and click Add Identity Source.

Enter a name for the identity source, such as corp.local.

Enter the domain name of your Active Directory server, such as DC=corp,DC=local.

Select Active Directory over LDAP as the type from the drop-down menu.

Click Set to configure LDAP servers. You can add up to three LDAP servers for failover support, to each domain.

Enter the hostname or IP address of your LDAP server, such as corpdcsrvr.corp.local.

Select LDAP as the protocol from the drop-down menu.

Enter the port number for the LDAP server, such as 389.

Click Connection Status to test the connection to the LDAP server. If successful, you will see a green check mark and a message saying "Connection successful".

Optionally, you can enable StartTLS to use encryption for the LDAP connection. To do this, toggle the Use StartTLS button and enter the certificate of the LDAP server in PEM format in the text box below.

Click Save to add the LDAP server.

Repeat steps 6 to 12 to add more LDAP servers if needed.

Enter the bind entry user name and password for the LDAP server, such as Administrator@corp.local and VMware1!.

Click Save to create the identity source.

Navigate to System > User Management > Users and Roles and click Add Role Assignment for LDAP.

Select corp.local as the domain from the drop-down menu.

Enter nsx-admin@corp.local in the search box and select it from the list that appears.

Select Enterprise Admin as the role from the drop-down menu.

Click Save to assign the role to the user.

[You have successfully integrated NSX Manager with LDAP and configured nsx-admin@corp.local Active Directory account as an Enterprise Admin access role.](#)

Question 5

Question Type: MultipleChoice

SIMULATION

Task 11

upon testing the newly configured distributed firewall policy for the Boston application. it has been discovered that the Boston-Web virtual machines can be "pinged" via ICMP from the main console. Corporate policy does not allow pings to the Boston VMs.

You need to:

* Troubleshoot ICMP traffic and make any necessary changes to the Boston application security

policy.

Complete the requested task.

Notes: Passwords are contained in the user _readme.txt. This task is dependent on Task 5.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To troubleshoot ICMP traffic and make any necessary changes to the Boston application security policy, you need to follow these steps:

Log in to the NSX Manager UI with admin credentials. The default URL is `https://<nsx-manager-ip-address>`.

Navigate to Security > Distributed Firewall and select the firewall policy that applies to the Boston application. For example, select Boston-web-Application.

Click Show IPSec Statistics and view the details of the firewall rule hits and logs. You can see which rules are matching the ICMP traffic and which actions are taken by the firewall.

If you find that the ICMP traffic is allowed by a rule that is not intended for it, you can edit the rule and change the action to Drop or Reject. You can also modify the source, destination, or service criteria of the rule to make it more specific or exclude the ICMP traffic.

If you find that the ICMP traffic is not matched by any rule, you can create a new rule and specify the action as Drop or Reject. You can also specify the source, destination, or service criteria of the rule to match only the ICMP traffic from the main console to the Boston web VMs.

After making the changes, click Publish to apply the firewall policy.

[Verify that the ICMP traffic is blocked by pinging the Boston web VMs from the main console again. You should see a message saying "Request timed out" or "Destination unreachable".](#)

Question 6

Question Type: MultipleChoice

SIMULATION

Task 5

You are asked to configure a micro-segmentation policy for a new 3-tier web application that will be deployed to the production environment.

You need to:

• Configure Tags with the following configuration detail:

Tag Name	Member
Boston	Boston-web-01a, Boston-web-02a, Boston-app-01a, Boston-db-01a
Boston-Web	Boston-web-01a, Boston-web-02a
Boston-App	Boston-app-01a
Boston-DB	Boston-db-01a

• Configure Security Groups (use tags to define group criteria) with the following configuration detail:

Boston
Boston Web-Servers
Boston App-Servers
Boston DB-Servers

• Configure the Distributed Firewall Exclusion List with the following configuration detail:

Virtual Machine:	core-A
------------------	--------

• Configure Policy & DFW Rules with the following configuration detail:

Policy Name:	Boston-Web-Application
Applied to:	Boston
New Services:	TCP-8443, TCP-3051

• Policy detail:

Rule Name	Source	Destination	Service	Action
Any-to-Web	Any	Boston Web-Servers	HTTP,HTTPS	ALLOW
Web-to-App	Boston Web-Servers	Boston App-Servers	TCP-8443	ALLOW
App-to-DB	Boston App-Servers	Boston DB-Servers	TCP-3051	ALLOW

Notes:

Passwords are contained in the user_readme.txt. Do not wait for configuration changes to be applied in this task as processing may take some time. The task steps are not dependent on one another. Subsequent tasks may require completion of this task. This task should take approximately 25 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

Step-by-Step Guide

Creating Tags and Security Groups

First, log into the NSX-T Manager GUI and navigate to Inventory > Tags to create tags like 'BOSTON-Web' for web servers and assign virtual machines such as BOSTON-web-01a and BOSTON-web-02

a. Repeat for 'BOSTON-App' and 'BOSTON-DB' with their respective VMs. Then, under Security > Groups, create security groups (e.g., 'BOSTON Web-Servers') based on these tags to organize the network logically.

Excluding Virtual Machines

Next, go to Security > Distributed Firewall > Exclusion List and add the 'core-A' virtual machine to exclude it from firewall rules, ensuring it operates without distributed firewall restrictions.

Defining Custom Services

Check Security > Services for existing services. If 'TCP-9443' and 'TCP-3051' are missing, create them by adding new services with the protocol TCP and respective port numbers to handle specific application traffic.

Setting Up the Policy and Rules

Create a new policy named 'BOSTON-Web-Application' under Security > Distributed Firewall > Policies. Add rules within this policy:

Allow any source to 'BOSTON Web-Servers' for HTTP/HTTPS.

Permit 'BOSTON Web-Servers' to 'BOSTON App-Servers' on TCP-9443.

Allow 'BOSTON App-Servers' to 'BOSTON DB-Servers' on TCP-3051. Finally, save and publish the policy to apply the changes.

This setup ensures secure, segmented traffic for the 3-tier web application, an unexpected detail being the need to manually create custom services for specific ports, enhancing flexibility.

Survey Note: Detailed Configuration of Micro-Segmentation Policy in VMware NSX-T Data Center 3.x

This note provides a comprehensive guide for configuring a micro-segmentation policy for a 3-tier web application in VMware NSX-T Data Center 3.x, based on the task requirements. The process involves creating tags, security groups, excluding specific virtual machines, defining custom services, and setting up distributed firewall policies. The following sections detail each step, ensuring a thorough understanding for network administrators and security professionals.

Background and Context

Micro-segmentation in VMware NSX-T Data Center is a network security technique that logically divides the data center into distinct security segments, down to the individual workload level, using network virtualization technology. This is particularly crucial for a 3-tier web application, comprising web, application, and database layers, to control traffic and enhance security. The task specifies configuring this for a production environment, with notes indicating

passwords are in user_readme.txt and no need to wait for configuration changes, as processing may take time.

Step-by-Step Configuration Process

Step 1: Creating Tags

Tags are used in NSX-T to categorize virtual machines, which can then be grouped for policy application. The process begins by logging into the NSX-T Manager GUI, accessible via a web browser with admin privileges. Navigate to Inventory > Tags, and click 'Add Tag' to create the following:

Tag name: 'BOSTON-Web', assigned to virtual machines BOSTON-web-01a and BOSTON-web-02a.

Tag name: 'BOSTON-App', assigned to BOSTON-app-01a.

Tag name: 'BOSTON-DB', assigned to BOSTON-db-01a.

This step ensures each tier of the application is tagged for easy identification and grouping, aligning with the attachment's configuration details.

Step 2: Creating Security Groups

Security groups in NSX-T are logical constructs that define membership based on criteria like tags, enabling targeted policy application. Under Security > Groups, click 'Add Group' to create:

Group name: 'BOSTON Web-Servers', with criteria set to include the 'BOSTON-Web' tag.

Group name: 'BOSTON App-Servers', with criteria set to include the 'BOSTON-App' tag.

Group name: 'BOSTON DB-Servers', with criteria set to include the 'BOSTON-DB' tag.

This step organizes the network into manageable segments, facilitating the application of firewall rules to specific tiers.

Step 3: Excluding 'core-A' VM from Distributed Firewall

The distributed firewall (DFW) in NSX-T monitors east-west traffic between virtual machines. However, certain VMs, like load balancers or firewalls, may need exclusion to operate without DFW restrictions. Navigate to Security > Distributed Firewall > Exclusion List, click 'Add', select 'Virtual Machine', and choose 'core-A'. Click 'Save' to exclude it, ensuring it bypasses DFW rules, as per the task's requirement.

Step 4: Defining Custom Services

Firewall rules often require specific services, which may not be predefined. Under Security > Services, check for existing services 'TCP-9443' and 'TCP-3051'. If absent, create them:

Click 'Add Service', name it 'TCP-9443', set protocol to TCP, and port to 9443.

Repeat for 'TCP-3051', with protocol TCP and port 3051.

This step is crucial for handling application-specific traffic, such as the TCP ports mentioned in

the policy type (TCP-9443, TCP-3051), ensuring the rules can reference these services.

Step 5: Creating the Policy and Rules

The final step involves creating a distributed firewall policy to enforce micro-segmentation. Navigate to Security > Distributed Firewall > Policies, click 'Add Policy', and name it 'BOSTON-Web-Application'. Add a section, then create the following rules:

Rule Name: 'Any-to-Web'

Source: Any (select 'Any' or IP Address 0.0.0.0/0)

Destination: 'BOSTON Web-Servers' (select the group)

Service: HTTP/HTTPS (predefined service)

Action: Allow

Rule Name: 'Web-to-App'

Source: 'BOSTON Web-Servers'

Destination: 'BOSTON App-Servers'

Service: TCP-9443 (custom service created earlier)

Action: Allow

Rule Name: 'App-to-DB'

Source: 'BOSTON App-Servers'

Destination: 'BOSTON DB-Servers'

Service: TCP-3051 (custom service created earlier)

Action: Allow

After defining the rules, click 'Save' and 'Publish' to apply the policy. This ensures traffic flows as required: any to web servers for HTTP/HTTPS, web to app on TCP-9443, and app to database on TCP-3051, while maintaining security through segmentation.

Additional Considerations

The task notes indicate no need to wait for configuration changes, as processing may take time, and steps are not dependent, suggesting immediate progression is acceptable. Passwords are in user_readme.txt, implying the user has necessary credentials. The policy order is critical, with rules processed top-to-bottom, and the attachment's 'Type: TCP-9443, TCP-3051' likely describes the services used, not affecting the configuration steps directly.

Table: Summary of Configuration Details

Component

Details

Tags

BOSTON-Web (BOSTON-web-01a, BOSTON-web-02a), BOSTON-App (BOSTON-app-01a), BOSTON-DB (BOSTON-db-01a)

Security Groups

BOSTON Web-Servers (tag BOSTON-Web), BOSTON App-Servers (tag BOSTON-App), BOSTON DB-Servers (tag BOSTON-DB)

DFW Exclusion List

Virtual Machine: core-A

Custom Services

TCP-9443 (TCP, port 9443), TCP-3051 (TCP, port 3051)

Policy Name

BOSTON-Web-Application

Firewall Rules

Any-to-Web (Any to Web-Servers, HTTP/HTTPS, Allow), Web-to-App (Web to App-Servers, TCP-9443, Allow), App-to-DB (App to DB-Servers, TCP-3051, Allow)

This table summarizes the configuration, aiding in verification and documentation.

Unexpected Detail

An unexpected aspect is the need to manually create custom services for TCP-9443 and TCP-3051, which may not be predefined, highlighting the flexibility of NSX-T for application-specific security policies.

Conclusion

This detailed process ensures a robust micro-segmentation policy, securing the 3-tier web application by controlling traffic **between** tiers and **excluding** specific VMs from DFW, aligning with best practices for network security in VMware NSX-T Data Center 3.x.

Question 7

Question Type: MultipleChoice

SIMULATION

Task 14

An administrator has seen an abundance of alarms regarding high CPU usage on the NSX Managers. The administrator has successfully cleared these alarms numerous times in the past and is aware of the issue. The administrator feels that the number of alarms being produced for these events is overwhelming the log files.

You need to:

* Review CPU Sensitivity and Threshold values.

Complete the requested task.

Notes: Passwords are contained in the user_readme.txt. This task is not dependent on other tasks. This task should take approximately 5 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To review CPU sensitivity and threshold values, you need to follow these steps:

Log in to the NSX Manager UI with admin credentials. The default URL is <https://<nsx-manager-ip-address>>.

Navigate to System > Settings > System Settings > CPU and Memory Thresholds.

You will see the current values for CPU and memory thresholds for NSX Manager, NSX Controller, and NSX Edge. These values determine the percentage of CPU and memory usage that will trigger an alarm on the NSX Manager UI.

You can modify the default threshold values by clicking Edit and entering new values in the text boxes. For example, you can increase the CPU threshold for NSX Manager from 80% to 90% to reduce the number of alarms for high CPU usage. Click Save to apply the changes.

[You can also view the historical data for CPU and memory usage for each component by clicking View Usage History. You can select a time range and a granularity level to see the usage trends and patterns over time](#)

Question 8

Question Type: MultipleChoice

SIMULATION

Task 10

You have been notified by the Web Team that they cannot get to any northbound networks from their Tampa web servers that are deployed on an NSX-T

network segment. The Tampa web VM's however can access each other.

You need to:

* Troubleshoot to find out why the Tampa web servers cannot communicate to any northbound networks and resolve the issue.

Complete the requested task. TO verify your work. ping the Control Center @ 192.168.110.10

Notes: Passwords are contained in the user_readme.txt. This task is dependent on Task 4. Some exam candidates may have already completed this task if they had done more than the minimum required in Task 4. This task should take approximately 15 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To troubleshoot why the Tampa web servers cannot communicate to any northbound networks, you need to follow these steps:

Log in to the NSX Manager UI with admin credentials. The default URL is `https://<nsx-manager-ip-address>`.

Navigate to Networking > Tier-0 Gateway and select the tier-0 gateway that connects the NSX-T network segment to the northbound networks. For example, select T0-GW-01.

Click Interfaces > Set and verify the configuration details of the interfaces. Check for any discrepancies or errors in the parameters such as IP address, subnet mask, MTU, etc.

If you find any configuration errors, click Edit and modify the parameters accordingly. Click Save to apply the changes.

If you do not find any configuration errors, check the connectivity and firewall rules between the tier-0 gateway and the northbound networks. You can use ping or traceroute commands from the NSX Edge CLI or the vSphere Web Client to test the connectivity. You can also use show service router command to check the status of the routing service on the NSX Edge.

If you find any connectivity or firewall issues, resolve them by adjusting the network settings or firewall rules on the NSX Edge or the northbound devices.

[After resolving the issues, verify that the Tampa web servers can communicate to any northbound networks by pinging the Control Center @ 192.168.110.10 from one of the web servers.](#)

Question 9

Question Type: MultipleChoice

SIMULATION

Task 8

You are tasked With troubleshooting the NSX IPSec VPN service Which has been reported down. Verify the current NSX configuration is deployed and resolve any issues.

You need to:

* Verify the present configuration as provided below:

NSX IPSec Session Name:	IPSEC
Remote IP:	192.168.140.2
Local Networks:	10.10.10.0/24
Remove Networks:	10.10.20.0/24
Pre-shared Key:	VMware!!VMware!!

Complete the requested task.

Notes: Passwords are contained in the user_readme.txt. This task is not dependent on another. This task Should take approximately 15 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To troubleshoot the NSX IPsec VPN service that has been reported down, you need to follow these steps:

Log in to the NSX Manager UI with admin credentials. The default URL is `https://<nsx-manager-ip-address>`.

Navigate to Networking > VPN > IPsec VPN and select the IPsec VPN session that is down. You can identify the session by its name, local endpoint, remote endpoint, and status.

Click Show IPsec Statistics and view the details of the IPsec VPN session failure. You can see the error message, the tunnel state, the IKE and ESP status, and the statistics of the traffic sent and received.

Compare the configuration details of the IPsec VPN session with the expected configuration as provided below. Check for any discrepancies or errors in the parameters such as local and remote endpoints, local and remote networks, IKE and ESP profiles, etc.

If you find any configuration errors, click Actions > Edit and modify the parameters accordingly. Click Save to apply the changes.

If you do not find any configuration errors, check the connectivity and firewall rules between the local and remote endpoints. You can use ping or traceroute commands from the NSX Edge CLI to test the connectivity. You can also use `show service ipsec` command to check the status of IPsec VPN service on the NSX Edge.

If you find any connectivity or firewall issues, resolve them by adjusting the network settings or firewall rules on the NSX Edge or the third-party device.

[After resolving the issues, verify that the IPsec VPN session is up and running by refreshing the IPsec VPN page on the NSX Manager UI. You can also use `show service ipsec sp` and `show service ipsec sa` commands on the NSX Edge CLI to check the status of security policy and security association for the IPsec VPN session.](#)

Question 10

Question Type: MultipleChoice

SIMULATION

Task 4

You are tasked with creating a logical load balancer for several web servers that were recently deployed.

You need to:

- Create a standalone Tier-1 gateway with the following configuration detail:

Name:	TI-LB
Linked Tier-0 Gateway:	None
Edge Cluster:	lb-edge-cluster
Service Interface:	Name: TI-LB IP Address / Mask: 192.168.220.10/24 Connected To (Segment): Columbus-LS
Static Route:	Add a default gateway to 192.168.220.1

- Create a load balancer and attach it to the newly created Tier-1 gateway with the following configuration detail:

Name:	web-lb
Size:	small
Attachment:	TI-LB

- Configure the load balancer with the following configuration detail:

- Create an HTTP application profile with the following configuration detail:

Name:	web-lb-app-profile
-------	--------------------

- Create an HTTP application profile with the following configuration detail:

Name:	web-lb-app-redirect-profile
Redirection:	HTTP to HTTPS Redirection

- Create an HTTP monitor with the following configuration detail:

Name	web-lb-monitor
Port:	80

- Create an L7 HTTP virtual server with the following configuration detail:

Name:	web-lb-virtual-server
IP Address:	192.168.220.20
Port:	80
Load Balancer:	web-lb
Server Pool:	None
Application Profile:	web-lb-app-redirect-profile

- Create an L4 TCP virtual server with the following configuration detail:

Name:	web-lb-virtual-server-https
IP Address:	192.168.220.20
Port:	443
Load Balancer:	web-lb
Server Pool:	Columbus-web-servers
Application Profile:	default-tcp-lb-app-profile

Complete the requested task.

Notes:

Passwords are contained in the user_readme.txt. Do not wait for configuration changes to be applied in this task as processing may take some time to complete. This task should take up to 35 minutes to complete and is required for subsequent tasks.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To create a logical load balancer for several web servers, you need to follow these steps:

Log in to the NSX Manager UI with admin credentials. The default URL is `https://<nsx-manager-ip-address>`.

Navigate to Networking > Load Balancing > Load Balancers and click Add Load Balancer.

Enter a name and an optional description for the load balancer. Select the tier-1 gateway where you want to attach the load balancer from the drop-down menu or create a new one by clicking New Tier-1 Gateway. Click Save.

Navigate to Networking > Load Balancing > Application Profiles and click Add Application Profile.

Enter a name and an optional description for the application profile. Select HTTP as the application type from the drop-down menu. Optionally, you can configure advanced settings such as persistence, X-Forwarded-For, SSL offloading, etc., for the application profile. Click Save.

Navigate to Networking > Load Balancing > Monitors and click Add Monitor.

Enter a name and an optional description for the monitor. Select HTTP as the protocol from the drop-down menu. Optionally, you can configure advanced settings such as interval, timeout, fall count, rise count, etc., for the monitor. Click Save.

Navigate to Networking > Load Balancing > Server Pools and click Add Server Pool.

Enter a name and an optional description for the server pool. Select an existing application profile from the drop-down menu or create a new one by clicking New Application Profile. Select an existing monitor from the drop-down menu or create a new one by clicking New Monitor. Optionally, you can configure advanced settings such as algorithm, SNAT translation mode, TCP multiplexing, etc., for the server pool. Click Save.

Click Members > Set > Add Member and enter the IP address and port number of each web server that you want to add to the server pool. For example, enter 192.168.10.10:80 and 192.168.10.11:80 for two web servers listening on port 80. Click Save and then Close.

Navigate to Networking > Load Balancing > Virtual Servers and click Add Virtual Server.

Enter a name and an optional description for the virtual server. Enter the IP address and port number of the virtual server that will receive the client requests, such as 10.10.10.100:80. Select HTTP as the service profile from the drop-down menu or create a new one by clicking New Service Profile. Select an existing server pool from the drop-down menu or create a new one by clicking New Server Pool. Optionally, you can configure advanced settings such as access log, connection limit, rate limit, etc., for the virtual server. Click Save.

[You have successfully created a logical load balancer for several web servers using NSX-T Manager UI.](#)

Question 11

Question Type: MultipleChoice

SIMULATION

Task 13

You have been asked to configure the NSX backups for the environment so that if the NSX Manager fails it can be restored with the same IP address to the original primary Data Center that is in an Active / Standby configuration. Backups should be scheduled to run once every 24 hours as well as when there are changes published to the NSX environment. Ensure that backups are completed on their respective environment. Verify the backup file has been created on the SFTP server.

* Credentials needed to complete the task:

SFTP User:	sftpuser
Password:	VMware!!
SFTP IP:	192.168.110.91
Hostname:	ubuntu-01.corp.local

You need to:

- * Verify that an SFTP server is available on the network and obtain SFTP Fingerprint.
- * Configure NSX Backups via NSX Appliance Backup
- * Configure Scheduling Criteria

Backup Configuration Criteria

Backup Schedule:	Once backup per 24 hours
Additional Backup Triggers:	Detect NSX configuration (5 min time interval)
Primary Data Center Configuration:	Active / Standby
Backup locations:	All backups on respective NSX environment
Additional Notes:	NSX Manager shall be restored with same IP address
Directory Path:	/data
Passphrase:	VMware!!

Complete the requested task.

Notes: Passwords are contained in the user_readme.txt. This task is not dependent on other tasks. This task should take approximately 15 minutes to complete.

Options:

A- See the Explanation part of the Complete Solution and step by step instructions

Answer:

A

Explanation:

To configure the NSX backups for the environment, you need to follow these steps:

Verify that an SFTP server is available on the network and obtain SFTP fingerprint. You can use the `search_web('SFTP server availability')` tool to find some information on how to set up and check an SFTP server. You can also use the `ssh-keyscan` command to get the fingerprint of the SFTP server. For example, `ssh-keyscan -t ecdsa sftp_server` will return the ECDSA key of the `sftp_server`. You can compare this key with the one displayed on the NSX Manager UI when you configure the backup settings.

Configure NSX Backups via NSX Appliance Backup. Log in to the NSX Manager UI with admin credentials. The default URL is `https://<nsx-manager-ip-address>`. Select System > Lifecycle Management > Backup & Restore. Click Edit under the SFTP Server label to configure your SFTP server. Enter the FQDN or IP address of the backup file server, such as 10.10.10.100. The protocol text box is already filled in. SFTP is the only supported protocol. Change the default port if necessary. The default TCP port is 22. In the Directory Path text box, enter the absolute directory path where the backups will be stored, such as `/dat`

a. The directory must already exist and cannot be the root directory (`/`). Avoid using path drive letters or spaces in directory names; they are not supported. In the Passphrase text box, enter a passphrase that will be used to encrypt and decrypt the backup files, such as `VMware1!`. Click Save to create the backup configuration.

Configure Scheduling Criteria. On the Backup & Restore page, click Edit under the Schedule label to configure your backup schedule. Select Enabled from the drop-down menu to enable scheduled backups. Select Daily from the Frequency drop-down menu to run backups once every 24 hours. Select a time from the Time drop-down menu to specify when the backup will start, such as 12:00 AM. Select Enabled from the Additional Backup Trigger drop-down menu to run backups when there are changes published to the NSX environment. Click Save to create the backup schedule.

Verify that a backup file has been created on the SFTP server. On the Backup & Restore page, click Start Backup to run a manual backup and verify that it completes successfully. You should see a message saying "Backup completed successfully". You can also check the status and details of your backups on this page, such as backup size, duration, and timestamp. Alternatively, you can log in to your SFTP server and check if there is a backup file in your specified directory path, such as `/data`.

To Get Premium Files for 3V0-41.22 Visit

<https://www.p2pexams.com/products/3v0-41.22>

For More Free Questions Visit

<https://www.p2pexams.com/vmware/pdf/3v0-41.22>

20%
DISCOUNT

P2P
exams